





Optical Fiber Adapter(FC,SC,ST,LC)

Features	
Low Insertion Loss High Repeatability	
Application	
LAN, Data network CATV Network Telecommunication	

Specifications:

Insertion Loss	≤0.2 dB
Plug and unplug force (g/f)	200-600
Durability	1000times
Operating Temperature	-40℃ to +75℃

PN	Description	Photo
AD-FC/SM-SP01	FC/PC adaptor (Small D-type)	 <p style="font-size: small;">FC Small D Adapter</p>
AD-FC/SM-SP02	FC/PC adaptor (Big D-type)	 <p style="font-size: small;">Big D type FC Adapter</p>
AD-FC/SM-SP03	FC/PC adaptor (Solid)	
AD-FC/SM-SP04	FC/PC adaptor (2 body)	

<p>AD-FC/SM-SP05</p>	<p>FC/PC adaptor (Oval)</p>	
<p>AD-FC/SM-SP06</p>	<p>FC/PC adaptor (Rectagular)</p>	
<p>AD-SC/SM-SP01</p>	<p>SC/PC Simplex Adapter</p>	
<p>AD-SC/SM-SP02</p>	<p>SC/PC Duplex Adapter</p>	
<p>AD-SC/SM-SP03</p>	<p>SC/APC Simplex Adapter</p>	
<p>AC-LC/SM-SP01</p>	<p>LC/PC simplex adapter</p>	

<p>AC-LC/SM-SP02</p>	<p>LC/PC Duplex adapter</p>	
<p>AD-LC/SM-SP04</p>	<p>LC/APC Simplex Adapter</p>	
<p>AD-ST/SM-SP01</p>	<p>ST/PC Simplex adapter</p>	
<p>AD-MPO/SM-SP01</p>	<p>MPO Adapter</p>	