

1260-1620nm All Band Wideband Coupler

Features	
Low excess loss & low IL & low PDL All Band operating Wavelength High stability and reliability	
Application	
Optical communication systems CATV FTTH / PON	

Specifications

Parameter		Grade P	Grade A
Operating wavelength (nm)		1260~1620	
Operating bandwidth (nm)		±80	
Typical excess loss (dB)		0.07	0.10
Insertion loss (dB)	50/50	≤3.8	≤4.0
	40/60	≤5.0/2.8	≤5.2/3.0
	30/70	≤6.4/2.0	≤6.7/2.2
	20/80	≤8.3/1.3	≤8.7/1.5
	10/90	≤11.5/0.7	≤12.0/0.8
	5/95	≤14.6/0.45	≤15.5/0.5
	2/98	≤18.8/0.3	≤19.5/0.4
PDL (dB)		≤0.15	≤0.20
Directivity (dB)		≥55	
Operating temperature ()		40 ~ +85	

Insertion Loss around 1380nm(water peak) is counted in the specifications above.

Package Information

Configuration	1x2 or 2x2		
Fiber length	1m, others on request		
Fiber Type	SMF-28e		
Pigtail type	250μm bare fiber	900μm loose tube	900μm/2mm/3mm loose tube
Dimensions(mm)	φ3.0×54 or φ3.0×40	φ3.0×54 φ3.0×56	90×14×8.5 or 90×16×9

Ordering Information

CP	Wavelength	Grade	Port Type	Wavelength (nm)	Coupling Ratio	Pigtail Type	Fiber Type	Length	Connector	Package	
	S = Single mode standard coupler	P	1x2	532	1/99	250=250um	1=SMF-28e	1=	NE=None	3x54	
		A	2x2	633	2/98	bare fiber	2=50/125	1m	FA=FC/APC	3x40	
	W =Wide band coupler		1x3	780	3/97	900=900um	3=62.5/12.5	X:other		FC=FC/UPC
			1x4	850	loose tube	4=HI1060FLE				
	D =Dual window coupler		1x5	980	50/50	2000=2mm	X			SA=SC/APC	
			1064		loose tube	5=Panda fiber				
	T =Three Window coupler				1310		3000=3mm			LC=LC/UPC	
					1550		loose tube				
	M =Multimode fiber Coupler				1310/1550					LA=LC/APC	
					1260~1620						
									XX=Others		